



PET(source)

(respirable)

FIBEROLASS - RESIN

Polu

TLV(source)

(inhalable)

www.olympus.com.ph

# Poly Klea MATERIAL SAFETY DATA SHEET

ACM BLUE GLASS FIBER E-WR/CSM COMBO MAT

# **SECTION 1- PRODUCT IDENTIFICATION**

- ACM BLUE GLASS FIBER E-WR/CSM COMBO MAT **PRODUCT** 

**MATERIAL** - FIBERGLASS

**FINISH** - NATURAL

# SECTION 2- HAZARDUS INGREDIENTS

MAX%(by weight) CHEMICAL UN# CAS# 98.7

fiberglass not assigned not assigned not listed not listed not known 5mg/m3 5mg/m3 fiberglass dust not assigned not assigned

AMOUNT WILL BE DEPENDENT UPON METHOD OF HANDLING

### **SECTION 3- OTHER INGREDIENTS**

ITEMS LISTED IN THIS SECTION ARE EITHER CHEMICALLY OR PHYSICALLY BONDED TO THE FIBERGLASS TEXTILE AND ARE DEEMED NON HAZARDOUS IN THE STATS SUPPLIED.

CHEMICAL AND CHEMICAL NAME MAX%(by weight)

Lubricants and humoctants

3.0

### **SECTION 4- PHYSICAL DATA**

: APPROX. 2.5 SPECIFIC GRAVITY

APPEARANCE/PHYSICAL STATE : WHITE/SOLID

: NO DISTINCTIVE ODOR **ODOR** 

# SECTION 5- FIRE HAZARD DATA

: NOT APPLICABLE FLASH POINT FLAMMABLE LIMITS : NOT APPLICABLE

: WATER/DRY POWDER OR FOAM (NEEDED FOR PACKAGING ONLY) EXTINGUISHING MEDIA

SPECIAL FIRE FIGHTING PROCEDURE : IN ANY SUSTAINED FIRE WEAR SELF-CONTAINED BREATHING

APPARATUS

<u>-</u>-

**USUAL FIRE HAZARDS** 

FIEERGLASS + RESIN

REAGLASS

: IN A SUSTAINED FIRE, COMBUSTIBLE DECOMPOSITION PRODUCTS MAYBE RELEASED, THESE PRODUCTS INCLUDE CARBON DIOXIDE, CARBON MONOXIDE AND LOW MOLECULAR WEIGHT HYDROCARBONS.



# LUZON:

REGIONAL OFFICE 1st Avenue, Sta. Maria Industrial Subd, Bagumbayan, Taguig City Tel.#: (02) 506-8519 ; 837-0710 837-0708



HEADQUARTERS

CEBU
2F SEA Olympus Building, AC Cortes Ave.
Trunkline #: (032) 421-7777
Tel.#: (032) 346-7137; 421-7800 to 06
421-7817 to 18; 421-7823
Fax #: (032) 421-7789; 346-1817



REGIONAL OFFICE Unit A16 J.King Warehouse Complex Km.3 Maa Road, Davao City 8000 Telefax #: (082) 244-1206; 302-2711

inquiry@olympus.com.ph







#### **SECTION 6- HEALTH HAZARD DATA**

POTENTIAL ROUTES OF ENTRY: INHALATION, SKIN CONTACT

EFFECTIVE OF OVEREXPOSURE: DIRECT SKIN CONTACT WITH FIBERGLASS OR ITS DUST MAY CAUSE

MECHANICAL IRRITATION AND TRANSITORY OF THE MOUTH, NOSE AND THROAT. TEXTILE SIZING NORMALLY BURN OFF OF THE SURFACE OF THE FIBERGLASS. THE FIRST TIME THE PRODUCT IS HEATED TO ABOUT 400F, IF

THIS OCCURS WITH INADEQUATE VENTILATION SOME SMOKE MAY ACCUMULATE CAUSING TEMPORARY IRRITATION OF THE EYES, NOSE AND

THROAT.



**EYES** 

SKIN

**CARCINOGEN** 

# **EMERGENCY AND FIRST AID ROCEDURE:**

INHALATION : MOVE TO FRESH AIR AREA **INGESTION** 

: NOT LIKELY TO OCCUR THROUGH NORMAL USE SHOULD INGESTION

OCCUR SEEK MEDICAL ATTENTION.

: FLUSH WITH FLOWING WATER FOR 15 MINUTES, SEEK MEDICAL

ATTENTION.

: FLUSH WITH AMPLE COOL WATER FOLLOWED BY WASHING

WITH MILD SOAP TO REMOVE ACCUMULATE FIBERS.

: NOT CLASSIFIED AS REGULATED UNDER ACGIH, IARC, NTP OF SHA. INDUSTRY STUDIES HAVE SHOWN TEXTILE GRADE FIBERGLASS TO BE

A NON-CARCINOGEN.

# **SECTION 7- SPECIAL PROTECTION REQUIRED**

EXPOSURE TO FIBERGLASS MAY CAUSE MECHANICAL IRRITATION TO THE SKIN, EYES, NOSE AND THROAT. TYPICALLY SUCH IRRITATION OCCURS TO NEWLY EXPOSED INDIVIDUALS AND USUALLY DIMINISHES AFTER SEVERAL DAYS OF EXPOSURE.

RESPIRATORY: IF AIRBORNE FIBERGLASS EXCEEDS THE REGULATORY LIMITS, OR IF UPPER RESPIRATORY IRRITATION OCCURS, USE A RESPIRATOR DESIGNED FOR NUISANCE TYPE DUST.







#### LUZON:

REGIONAL OFFICE 1st Avenue, Sta. Maria Industrial Subd. Bagumbayan, Taguig City Tel.#: (02) 506-8519 ; 837-0710 837-0708



**HEADQUARTERS** CEBU
2F SEA Olympus Building, AC Cortes Ave.
Trunkline #: (032) 421-7777
Tel.#: (032) 346-7137; 421-7800 to 06
421-7817 to 18; 421-7823
Fax #: (032) 421-7789; 346-1817



# MINDANAO:

REGIONAL OFFICE Unit A16 J.King Warehouse Complex Km.3 Maa Road, Davao City 8000 Telefax #: (082) 244-1206; 302-2711







TECHNICAL DATA SHEET

ACM BLUE GLASS FIBER E-WR/CSM COMBO MAT

PRODUCT NAME: ACM BLUE GLASS FIBER

Material code: E-WR/CSM1050

Type: *E-glass* **DESCRIPTION** 

**Combo Mat** is a fabric made by Woven Roving with Chopped Strand Mat connecting through stitch yarn and is mainly used for hand lay-up process or mechanical process for large, high-strength FRP products such as boats, railroad carriages, storage tanks and architectural structures, etc. The roving sizing system of combo mat is silane and specification 1058g/m² or 1,250 mm or 1,270 mm, compatible with polyester, vinyl ester and epoxy resin.

#### **PROPERTIES**

- 1. Silane coupling
- 2. Fast wet-out
- 3. High mechanical strength
- 4. Good moldability

# TECHNICAL CHARACTERISTICS

Item	Standard Value	Test Method
Area weight (g/m <sup>2</sup> )	± 7%	ISO3374
oluklear	$EWR600g/m^2 + CSM450g/cm^2$	Polulita
	Stitch yarn 8g/m <sup>2</sup>	
Loss on ignition (%)	1-7	ISO1887
Moisture content (%)	≤ 0.15	ISO3344
Width (mm)	1,270±10	ISO5025
Roll weight (kg)	50	NA

# **Packaging**

Each roll in PE bag and then put into carton and pallet.

# **Product storage**

Unless otherwise specified, it should be stored in a cool, dry, water-proof area. Avoid dust and dampness. Keep room temperature at 15-35\mathbb{\tilde{M}} and humidity at 35-65\%, respectively.

SEA Olympus Marketing, Inc. reserves the right to change the information given herein without prior notice. We believe this information to be reliable, but do not guarantee its applicability to the user's process or assume liability for occurrence arising out of its use. The user, by accepting products described herein agrees to be responsible for thoroughly testing any application before committing to production. ©20

# LUZON:

REGIONAL OFFICE TAGUIG 1st Avenue, Sta. Maria Industrial Subd, Bagumbayan, Taguig City Tel.#: (02) 506-8519; 837-0710 837-0708

# VISAYAS:

HEADQUARTERS
CEBU
2F SEA Olympus Building, AC Cortes Ave.
Trunkline #: (032) 421-7777
Tel.#: (032) 346-7137; 421-7800 to 06
421-7817 to 18; 421-7823
Fax #: (032) 421-7789; 346-1817

#### MINDANAO:

REGIONAL OFFICE DAVAO Unit A16 J.King Warehouse Complex Km.3 Maa Road, Davao City 8000 Telefax #: (082) 244-1206; 302-271

inquiry@olympus.com.ph