



S.E.A.

OLYMPUS
Marketing, Inc.

www.olympus.com.ph

Poly Klear®
FIBERGLASS + RESIN

Poly Klear®
FIBERGLASS + RESIN

Poly Klear®
FIBERGLASS + RESIN

Poly Klear®
FIBERGLASS + RESIN

MATERIAL SAFETY DATA SHEET

POLYKLEAR MOLD RELEASE WAX LIQUID

Product name :
Chemical Nature :

POLYKLEAR MOLD RELEASE WAX LIQUID
Petroleum waxes dispersed in mineral spirit

1. PHYSICAL DATA

Physical Form : Soft Paste
Odor : distinct
Boiling Point : Approx. 80 °C
Solidification Point : -15°C
Solubility in water : immiscible
% solid : 30±1
Spec. Gravity : 0.8

2. STORAGE AND HANDLING

Special precautions on transport and storage : avoid expose to heat or fire
Hazardous decomposition products : None
Hazardous reaction : None
Protective precautions : Skin and eye protection
Shelf life : 6 months
Procedure on spillage and leakage : Soak up with absorbent materials
Disposal : Dispose in accordance with local Regulations

LUZON:

REGIONAL OFFICE
TAGUIG
1st Avenue, Sta. Maria Industrial Subd,
Bagumbayan, Taguig City
Tel.#: (02) 506-8519 ; 837-0710
837-0708

VISAYAS:

HEADQUARTERS
CEBU
2F SEA Olympus Building, AC Cortes Ave.
Trunkline #: (032) 421-7777
Tel.#: (032) 346-7137 ; 421-7800 to 06
421-7817 to 18 ; 421-7823
Fax #: (032) 421-7789 ; 346-1817

MINDANAO:

REGIONAL OFFICE
DAVAO
Unit A16 J.King Warehouse Complex
Km.3 Maa Road, Davao City 8000
Telefax #: (082) 244-1206 ; 302-2711

✉ inquiry@olympus.com.ph



S.E.A.

OLYMPUS
Marketing, Inc.

www.olympus.com.ph

Poly Klear
FIBERGLASS + RESIN

Poly Klear
FIBERGLASS + RESIN

Poly Klear
FIBERGLASS + RESIN

Poly Klear
FIBERGLASS + RESIN

3. IGNITION AND COMBUSTION DATA

Flash Point	:	Above 80°C
Ignition Temp.	:	Not Available
Extinguishing Media	:	Water Spray, Foam, CO ₂ & dry Powder
Special Fire Precautions	:	None

Poly Klear
FIBERGLASS + RESIN

Poly Klear
FIBERGLASS + RESIN

4. EMERGENCY AND FIRST-AID PROCEDURES

Skin	:	Wash with water
Eyes	:	Wash with running water (eyelids open) Consult a physician.
Ingestion	:	Symptomatic treatment
Inhalation	:	Breathe fresh air

Poly Klear
FIBERGLASS + RESIN

Poly Klear
FIBERGLASS + RESIN

5. ADDITIONAL INFORMATION

This product should be stored, handled and used in accordance with good industrial hygienic and safety practices and in conformity with any legal regulations.

Poly Klear
FIBERGLASS + RESIN

Poly Klear
FIBERGLASS + RESIN

Poly Klear
FIBERGLASS + RESIN

The data and information contained in this Material Safety Data Sheet is provided to the best of our knowledge and ability on existing hazards, properties and handling of this product as recommended. It is recommended that the user tests the product according to its purpose. The user is responsible for the proper, safe and lawful use of this product. The information contained in this MSDS is subject to change without further notice. © 20

LUZON:

REGIONAL OFFICE
TAGUIG
1st Avenue, Sta. Maria Industrial Subd,
Bagumbayan, Taguig City
Tel.#: (02) 506-8519 ; 837-0710
837-0708

Poly Klear
FIBERGLASS + RESIN
VISAYAS:
HEADQUARTERS
CEBU
2F SEA Olympus Building, AC Cortes Ave.
Trunkline #: (032) 421-7777
Tel.#: (032) 346-7137 ; 421-7800 to 06
421-7817 to 18 ; 421-7823
Fax #: (032) 421-7789 ; 346-1817

MINDANAO:

REGIONAL OFFICE
DAVAO
Unit A16 J.King Warehouse Complex
Km.3 Maa Road, Davao City 8000
Telefax #: (082) 244-1206 ; 302-2711

✉ inquiry@olympus.com.ph



S.E.A.

OLYMPUS
Marketing, Inc.

www.olympus.com.ph

Poly Klear®
FIBERGLASS + RESIN

Poly Klear®
FIBERGLASS + RESIN

Poly Klear®
FIBERGLASS + RESIN

Poly Klear®
FIBERGLASS + RESIN

Technical Data Sheet

POLYKLEAR MOLD RELEASE WAX LIQUID

PRODUCT

Liquid Release Wax is a petroleum based mixed waxes intended for mould release and lubrication.

SPECIFICATIONS

Appearance: Soft yellowish paste

Boiling Point: 152 - 200 °C

Flash Point: 40 °C (Abel)

Specific Gravity: 0.766 - 0786 @ 20 °C

HEALTH INFORMATION AND PROTECTION

Skin Contact:

Remove contaminated clothing. Immediately flush skin with large amounts of water for at least 15 minutes, and follow by washing with soap and water if available.

Eye Contact:

Immediately flush eyes with large amounts of water for at least 10 minutes while holding eyelids open. Transport to the nearest medical facility for additional treatment.

STORAGE and HANDLING

Must be stored in a diked (bonded) well-ventilated area, away from sunlight, ignition sources, and other sources of heat. Bulk storage tanks should be diked (bonded). Keep away from aerosols, flammables, oxidizing agents, corrosives. Storage Temperature: Ambient, and dispose in compliance with local disposal regulations.

The information contained in this product specification sheet has been provided based on laboratory results. The type, quality and characteristics of substrates used, the environment of the end-user, individual systems or processes employed by the end-user and other conditions are elements which are beyond our control and we therefore recommend that the end-user test the product for the specific application; substrate required under the end-users environment and other working conditions. SEA Olympus Mktg, Inc. will not be held liable for damages due to the improper use of our products. All information stated above is subject to change without prior notice. ©20

REGIONAL OFFICE TAGUIG

1st Avenue, Sta. Maria Industrial Subd,
Bagumbayan, Taguig City
Tel.#: (02) 506-8519 ; 837-0710
837-0708

HEADQUARTERS CEBU

2F SEA Olympus Building, AC Cortes Ave.
Trunkline #: (032) 421-7777
Tel.#: (032) 346-7137 ; 421-7800 to 06
421-7817 to 18 ; 421-7823
Fax #: (032) 421-7789 ; 346-1817

REGIONAL OFFICE DAVAO

Unit A16 J.King Warehouse Complex
Km.3 Maa Road, Davao City 8000
Telefax #: (082) 244-1206 ; 302-2711

✉ inquiry@olympus.com.ph