



Material Safety Data Sheet

POLYKLEAR IS-BR25 SILICONE RUBBER

Section 1 - Identification of the substance/preparation and of the company/undertaking 1.1 Product identifier

Product name: POLYKLEAR IS-BR25 SILICONE RUBBER

Item No.: IS-CR05, IS-CR10, IS-CR15, IS-CR20, IS-CR25, IS-CR30, IS-CR35, IS-CR40,

IS-HCR05, IS-HCR10, IS-HCR15, IS-HCR20, IS-HCR25, IS-HCR30, IS-HCR35,

IS-HCR40, IS-HCR50, IS-HCR60, IS-HCR70, IS-ECR15

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses: Mold making Uses advised against: Not available.

Section 2 - Hazards Identification

2.1. Classification of the substance or mixture

2.1.1 Classification according to Regulation (EC) No. 1272/2008 [CLP]

Not classified as dangerous goods.

2.2. Label elements

Not available.

2.3. Other hazards

Burn & Burst danger: This product is not flammable.

Human health and environment: Liquid silicon rubber is harmless to human health and the

environment.

Section 3-Composition/Information on Ingredient

3.1. Mixtures

Ingredient	CAS No.	Weight (%)
Dimethyl siloxane	63148-62-9	35 PoluKies
Silicone dioxide powder	14808-60-7	35 FIBENGLASS + H
Polydimethylsiloxane	68083-19-2	30





REGIONAL OFFICE TAGUIG 1st Avenue, Sta. Maria Industrial Subd, Bagumbayan, Taguig City Tel.#: (02) 506-8519 ; 837-0710 837-0708



HEADQUARTERS

Trunkline #: (032) 421-7777
Tel.#: (032) 346-7137; 421-7800 to 06
421-7817 to 18; 421-7823
Fax #: (032) 421-7789; 346-1817



REGIONAL OFFICE DAVAO Unit A16 J.King Warehouse Complex Km.3 Maa Road, Davao City 8000 Telefax #: (082) 244-1206; 302-2711





www.olympus.com.ph

Section 4 - First Aid Measures

4.1. Description of first aid measures

General notes: First aid is not generally necessary for normal use.

Remove from exposure and move to fresh air immediately. Get medical aid.

■ Skin contact

If cause skin irritation, wash with water and soap. Get medical aid.

■ Eve contact

Flush eyes with plenty of water for at least 15 minutes, occasionally lifting the upper and lower eyelids. Get medical aid.

Ingestion

Rinse mouth and spit the liquid. Call a physician if you fell unwell.

Section 5 – Fire Fighting Measures

5.1. Extinguishing media

Suitable extinguishing media: Use extinguishers suitable for surroundings.

5.2. Special hazards arising from the mixture

Burn & Burst danger: This product is not flammable.

Hazardous combustion products: Carbon monoxide, carbon dioxide.

5.3. Advice for firefighters

Wear self-contained breathing apparatus.

Put the fire out in upwind direction.

Shut off sources of ignition.

Section 6 - Accidental Release Measures

6.1. Personal precautions, protective equipment and emergency procedures

Emergency procedures: Evacuate personnel to safe areas.

Protective equipment: Wear hand protection and body protection.

6.2. Environmental precautions

Low hazard to waters. Inform the responsible authorities when very large quantities get into water, drainage, sewer, or the ground.

6.3. Methods and material for containment and cleaning up

Absorb or cover spillage with sand or incombustible material. Or clean with plenty of water and let out the diluted solution into the wastewater system.

6.4. Reference to section 8 and section 13.

Section 7 - Handling and Storage 7.1. Precautions for safe handling

LUZON:

REGIONAL OFFICE TAGUIG 1st Avenue, Sta. Maria Industrial Subd, Bagumbayan, Taguig City Tel.#: (02) 506-8519; 837-0710

VISAYAS:

HEADQUARTERS

CEBU 2F SEA Olympus Building, AC Cortes Ave. Trunkline #: (032) 421-7777 Tel.#: (032) 346-7137 ; 421-7800 to 06 421-7817 to 18 ; 421-7823 Fax #: (032) 421-7789 ; 346-1817

MINDANAO:

REGIONAL OFFICE DAVAO Unit A16 J.King Warehouse Complex Km.3 Maa Road, Davao City 8000 Telefax #: (082) 244-1206; 302-2711





www.olympus.com.ph

Containers have to be labeled clearly and permanently. Do not leave container open.

Store in the original container as much as possible.

Preventing leaks is one of the major issues, as liquid molding compounds can seep through gaps in the machine and impede operations.

7.2. Conditions for safe storage, including any incompatibilities

Keep container tightly sealed in a dry, cool and well-ventilated place.

Do not let impurities such as water, acids and alkalis enter into the container.

Avoid direct sunlight.

Storage period is 10 months.

Section 8 - Exposure Controls, Personal Protection

8.1. Control parameters

Not established.

8.2. Exposure controls

8.2.1 Appropriate engineering controls

Prevent leaks. Well ventilated.

8.2.2 Personal Protection

Gloves

8.2.3 Other Protective Clothing or Equipment

Not necessary under conditions of normal use.

Section 9 - Physical and Chemical Properties

9.1. Information on basic physical and chemical properties

Form: Thick liquid.

Solubility in water: Insoluble

Section 10 - Stability and Reactivity

10.1. Chemical stability

The mixture is considered stable.

10.2. Possibility of hazardous reactions

Hazardous polymerization will not occur.

10.3. Conditions to avoid

Direct sunlight.

10.4. Incompatible materials



HEADQUARTERS

Trunkline #: (032) 421-7777
Tel.#: (032) 346-7137; 421-7800 to 06
421-7817 to 18; 421-7823
Fax #: (032) 421-7789; 346-1817

MINDANAO:

REGIONAL OFFICE DAVAO Unit A16 J.King Warehouse Complex

Km.3 Maa Road, Davao City 8000 Telefax #: (082) 244-1206; 302-2711 inquiry@olympus.com.ph

837-0708









LUZON:

REGIONAL OFFICE TAGUIG 1st Avenue, Sta. Maria Industrial Subd, Bagumbayan, Taguig City Tel.#: (02) 506-8519 ; 837-0710





www.olympus.com.ph

Acids, alkalis, oxidizing agents.

Section 11 - Toxicological Information 11.1. Information on toxicological effects

Acute toxicity: None

Serious eye damage/irritation: May cause slight eye irritation.

Respiratory or skin sensitisation: None.

Germ cell mutagenicity: None

Carcinogenicity: None

Section 12 - Ecological Information

12.1. Toxicity

None

12.2. Persistence and degradability

None

2.3. Bioaccumulative potential

None

12.4. Mobility in soil

None

12.5. Results of PBT and vPvB assessment

None

12.6. Other adverse effects

Low hazard to waters.

Section 13 - Disposal Considerations

Reduce the release of the mixture to the environment, such as avoiding spills or keeping away from drains.

Consult manufacturer for recycling options or consult local or regional waste management

authority for disposal if no suitable treatment or disposal facility can be identified.

Section 14 - Transport Information

Not regulated for transport of dangerous goods: UN, IATA, IMDG.

Section 15 - Regulatory Information

This safety datasheet complies with the requirements of Regulation (EC) No. 1907/2006.

Section 16 - Other Information

The above information is based on the data of which we are aware and is believed to be correct

LUZON:

REGIONAL OFFICE 1st Avenue, Sta. Maria Industrial Subd, Bagumbayan, Taguig City Tel.#: (02) 506-8519 ; 837-0710 837-0708

VISAYAS:

HEADQUARTERS

CEBU 2F SEA Olympus Building, AC Cortes Ave. Trunkline #: (032) 421-7777 Tel.#: (032) 346-7137; 421-7800 to 06 421-7817 to 18; 421-7823 Fax #: (032) 421-7789; 346-1817

MINDANAO:

REGIONAL OFFICE DAVAO Unit A16 J.King Warehouse Complex Km.3 Maa Road, Davao City 8000 Telefax #: (082) 244-1206; 302-2711







of the data hereof. Since this information may be applied under conditions beyond our control and with which may be unfamiliar and since data made available subsequent to the data hereof may suggest modifications of the information, we do not assume any responsibility for the results As of its use. This information is furnished upon condition that the person receiving it shall make his own determination of the suitability of the material for his particular purpose.

APPENDIX 1: Glossary / List of acronyms LIST OF ACRONYMS

	-I 7	design Delu /de	
	CLP	Classification Labeling Packaging Regulation (EC) No 1272/2008	
	CAS No.	AS No. Chemical Abstracts Service number	
	UN	United Nations	
	IATA	International Air Transport Association	
n.	IMDG	International Maritime Dangerous Goods	











LUZON:

REGIONAL OFFICE 1st Avenue, Sta. Maria Industrial Subd. Bagumbayan, Taguig City Tel.#: (02) 506-8519 ; 837-0710 837-0708



HEADQUARTERS
CEBU
2F SEA Olympus Building, AC Cortes Ave.
Trunkline #: (032) 421-7777
Tel.#: (032) 346-7137; 421-7800 to 06
421-7817 to 18; 421-7823
Fax #: (032) 421-7789; 346-1817

REGIONAL OFFICE DAVAO Unit A16 J.King Warehouse Complex Km.3 Maa Road, Davao City 8000 Telefax #: (082) 244-1206; 302-2711









POLYKLEAR IS-BR25 SILICONE RUBBER

Description

brushing type condensation silicone rubber for molding. BR25 is similar with RTV585 and RTV586. It has exceptional working properties and library life. POLYKLEAR IS-BR25 SILICONE RUBBER Series offer different grades in hardness, viscosity, tear and tensile strength for different applications.

POLYKLEAR IS-BR25 SILICONE RUBBER Series represent POLYKLEAR's

- Key features
- ★ Reproduce fine details for any sizes of products
- ★ Proper and customized viscosity for brushing molds
- ★ Mostly use for brushing purpose or casting for large size of products
- ★ Excellent tear and tensile strength, good elongation
- ★ Ideal molding material for casting, optimal material to replace PU molds
- ★ Maximize your duplication times

Applications

POLYKLEAR IS-BR Series are suitable for a variety of industrial and art related applications including making molds to reproduce prototypes, furniture, sculpture, concrete, plaster, gypsum fiber glass, wax/candle crafts, toys, soap, artificial stones, cement decoration, GRC, GRG and also food product items, where high temperature resistance, food grade are not required.

Optional Accessories

Silicone Pigment | Thinner | Mixer Machine | Vacuum Machine

Physical Properties Test @25℃	IS-BR25
Hardness (Shore A)	24~25
Mixing ration (by weight)	100A:2~4B
Color	White
Mixed Viscosity (cps)	35,000~36,000
Working time (Mins)	22"(Blue) 46"(Clear)
De-mold time (Hrs)	4~8
Tear Strength (KN/m)	≥28
Tensile Strength (Mpa)	≥3.9
Elongation (%)	550~580

Packing

25KG/Pail

Storage & shelf-life

12 months, stored in a dry & cool place under temperature 25 , with seal

LUZON:

REGIONAL OFFICE 1st Avenue, Sta. Maria Industrial Subd. Bagumbayan, Taguig City Tel.#: (02) 506-8519; 837-0710

VISAYAS:

HEADQUARTERS

CEBU 2F SEA Olympus Building, AC Cortes Ave. Trunkline #: (032) 421-7777 Tel.#: (032) 346-7137; 421-7800 to 06 421-7817 to 18; 421-7823 Fax #: (032) 421-7789; 346-1817

MINDANAO:

REGIONAL OFFICE Unit A16 J.King Warehouse Complex Km.3 Maa Road, Davao City 8000 Telefax #: (082) 244-1206; 302-2711